

OFFSET OPTIC MOUNT - ARISAKA DEFENSE PLATE #10 TALL HEIGHT (1.9"-2.2") OPTIC PLATE

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Rifle Bases](#)

The Patent Pending Arisaka Offset Optic Mount is a modular mounting solution that allows the user to select a 35 or 45 degree offset position for a red dot sight without requiring additional components. The 35 degree position brings the red dot sight up closer to slimmer, smaller scopes, while the 45 degree position provides additional clearance around wider turrets or larger, higher magnification scopes. The Arisaka Offset Optic Mount is designed to be attached to the top Picatinny rail of an AR15 rifle. When the rifle is canted to make use of the offset red dot sight, the optic remains centered over the bore and maintains a lower 1/3 co-witness height. The base and optic plates can be reversed, allowing for use on the left or right side. The base and plates can each be purchased separately or as a combination, providing an upgrade path in the future as users acquire new red dot sights. Weight: 1.9 oz without optic. Length: 1.0" for the base, which occupies three Picatinny slots (twin recoil lugs and clamping screw). Height: The base sits 0.180" above the surface of the Picatinny rail. The mount is CNC machined from 6061-T6 aluminum and MIL-A-8625 Type III hard coat anodized. IP20 and IP27 Torx Plus bit drivers are included with each base. Standard height (for 1.5" to 1.8" scope mounts): Plate 1: Docter, Eotech MRDS, Insight, Meopta, Vortex Venom/Viper, Burris Fastfire III Plate 2: Trijicon RMR, SRO, Holosun 407C, 507C, 508T, Swampfox Kingslayer, Liberty, Justice Plate 4: Leupold Delta Point Pro, JPoint, Shield RMS, RMSc, Swampfox Sentinel, SIG Romeo Zero Plate 5: Aimpoint Micro T1/T2/H1/H2, SIG Romeo 4, 5 (not 5X), Holosun HS403 (not A), HS503, HS515, HS530 Plate 6: Aimpoint Acro Tall height (1.9" to 2.2" scope mounts): Plate 7: Docter, Eotech MRDS, Insight, Meopta, Vortex Venom/Viper, Burris Fastfire III Plate 8: Trijicon RMR, SRO, Holosun 407C, 507C, 508T Plate 10: Leupold Delta Point Pro, JPoint, Shield RMS, RMSc, Swampfox Sentinel, SIG Romeo Zero Plate 11: Aimpoint Micro T1/T2/H1/H2, SIG Romeo 4, 5 (not 5X), Holosun HS403 (not A), HS503, HS515, HS530 Plate 12: Aimpoint Acro



Attributes

- Name: [ARISAKA DEFENSE PLATE #10 TALL HEIGHT \(1.9"-2.2"\) OPTIC PLATE](#)
- Manufacturer: [ARISAKA DEFENSE](#)
- Product no.: 100040230
- Mfr. No.: OOM-P10
- Bullet Style: -
- Caliber: -
- Colour: Black
- Diameter (in): -
- Fits / Used For: -
- Grain: -
- Material: -
- Number of Bases: -
- Style: -
- Delivery weight: 0.034kg
- Shipping height: 25mm
- Shipping width: 51mm
- Shipping length: 102mm

- UPC: 601557939791

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for OFFSET OPTIC MOUNT ARISAKA DEFENSE PLATE #10 TALL HEIGHT (1.9"2.2") OPTIC PLATE
- About Us

Safety Instruction Guide for OFFSET OPTIC MOUNT ARISAKA DEFENSE PLATE #10 TALL HEIGHT (1.9"2.2") OPTIC PLATE

Introduction

Thank you for choosing the OFFSET OPTIC MOUNT ARISAKA DEFENSE PLATE #10. This product is designed to enhance your shooting experience by providing a modular and adjustable mounting solution for your red dot sight. This guide will provide essential safety information, usage instructions, and contact information for further support.

General Safety Guidelines

- Ensure the optic mount is compatible with your firearm and optic before installation.
- Always handle firearms and accessories with care and follow all safety protocols.
- Keep the product out of reach of children and unauthorized users.
- Regularly inspect the mount for any signs of wear or damage before use.
- Do not exceed the recommended weight limit for the optic mount.
- Report any unsafe conditions or incidents to the appropriate authorities.

Specific Safety Precautions for Use

- Always ensure the rifle is unloaded before installing or adjusting the optic mount.
- Use appropriate tools for installation to avoid damaging the mount or the firearm.
- Ensure that the optic is securely attached to the mount before use.
- When using the offset red dot sight, make sure the rifle is properly supported to prevent accidents.
- Be aware of your surroundings and ensure a clear line of sight when using the optic mount.
- Avoid using the mount in extreme temperatures or harsh environmental conditions that could affect its performance.

Instructions for Installation and Usage

1. Installation

- Ensure the firearm is unloaded and pointed in a safe direction.
- Locate the top Picatinny rail on your AR15 rifle.
- Align the base of the OFFSET OPTIC MOUNT with the desired position on the rail.
- Secure the mount using the provided clamping screw and ensure it is tightened to prevent movement.
- Attach the appropriate optic plate based on your specific red dot sight model.
- If necessary, reverse the base and plates to accommodate left or rightside use.

2. Usage

- When using the offset red dot sight, cant the rifle to the side as needed.
- Ensure the optic remains centered over the bore for accurate aiming.
- Maintain a lower 1/3 cowitness height for optimal sight alignment.
- Regularly check the tightness of the mount and optic to ensure they remain secure during use.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in regular household waste.
- Consider recycling components where possible to minimize environmental impact.

Contact Information for Further Support

For any questions or concerns regarding the OFFSET OPTIC MOUNT ARISAKA DEFENSE PLATE #10, please refer to the manufacturer's website or customer support channels for assistance.

Thank you for choosing Arisaka Defense. Your safety and satisfaction are our top priorities.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk