

OFFSET OPTIC MOUNT - ARISAKA DEFENSE PLATE #11 TALL HEIGHT (1.9"-2.2") OPTIC PLATE

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Rifle Bases](#)

The Patent Pending Arisaka Offset Optic Mount is a modular mounting solution that allows the user to select a 35 or 45 degree offset position for a red dot sight without requiring additional components. The 35 degree position brings the red dot sight up closer to slimmer, smaller scopes, while the 45 degree position provides additional clearance around wider turrets or larger, higher magnification scopes. The Arisaka Offset Optic Mount is designed to be attached to the top Picatinny rail of an AR15 rifle. When the rifle is canted to make use of the offset red dot sight, the optic remains centered over the bore and maintains a lower 1/3 co-witness height. The base and optic plates can be reversed, allowing for use on the left or right side. The base and plates can each be purchased separately or as a combination, providing an upgrade path in the future as users acquire new red dot sights. Weight: 1.9 oz without optic. Length: 1.0" for the base, which occupies three Picatinny slots (twin recoil lugs and clamping screw). Height: The base sits 0.180" above the surface of the Picatinny rail. The mount is CNC machined from 6061-T6 aluminum and MIL-A-8625 Type III hard coat anodized. IP20 and IP27 Torx Plus bit drivers are included with each base. Standard height (for 1.5" to 1.8" scope mounts): Plate 1: Docter, Eotech MRDS, Insight, Meopta, Vortex Venom/Viper, Burris Fastfire III Plate 2: Trijicon RMR, SRO, Holosun 407C, 507C, 508T, Swampfox Kingslayer, Liberty, Justice Plate 4: Leupold Delta Point Pro, JPoint, Shield RMS, RMSc, Swampfox Sentinel, SIG Romeo Zero Plate 5: Aimpoint Micro T1/T2/H1/H2, SIG Romeo 4, 5 (not 5X), Holosun HS403 (not A), HS503, HS515, HS530 Plate 6: Aimpoint Acro Tall height (1.9" to 2.2" scope mounts): Plate 7: Docter, Eotech MRDS, Insight, Meopta, Vortex Venom/Viper, Burris Fastfire III Plate 8: Trijicon RMR, SRO, Holosun 407C, 507C, 508T Plate 10: Leupold Delta Point Pro, JPoint, Shield RMS, RMSc, Swampfox Sentinel, SIG Romeo Zero Plate 11: Aimpoint Micro T1/T2/H1/H2, SIG Romeo 4, 5 (not 5X), Holosun HS403 (not A), HS503, HS515, HS530 Plate 12: Aimpoint Acro



Attributes

- Name: [ARISAKA DEFENSE PLATE #11 TALL HEIGHT \(1.9"-2.2"\) OPTIC PLATE](#)
- Manufacturer: [ARISAKA DEFENSE](#)
- Product no.: 100040231
- Mfr. No.: OOM-P11
- Colour: Black
- Delivery weight: 0.036kg
- Shipping height: 25mm
- Shipping width: 51mm
- Shipping length: 102mm
- UPC: 601557939753

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for OFFSET OPTIC MOUNT ARISAKA DEFENSE PLATE #11 TALL HEIGHT \(1.9"2.2"\) OPTIC PLATE](#)
- [About Us](#)

Safety Instruction Guide for OFFSET OPTIC MOUNT ARISAKA DEFENSE PLATE #11 TALL HEIGHT (1.9"2.2") OPTIC PLATE

Introduction

Thank you for choosing the Arisaka Offset Optic Mount. This guide provides essential safety instructions and usage guidelines to ensure your product is used safely and effectively. Please read this document carefully before installation and use.

General Safety Guidelines

- Ensure that the product is compatible with your firearm and optic before installation.
- Always follow local laws and regulations regarding firearm accessories.
- Inspect the product for any damage or defects before use. Do not use if damaged.
- Keep the product out of reach of children and vulnerable individuals.
- Use the product only for its intended purpose as specified in the product information.
- Regularly check the mounting screws and components for tightness and wear.
- If you experience any issues during installation or use, cease use immediately and consult a qualified professional.

Specific Safety Precautions for Use

- When using the offset optic mount, ensure that the firearm is pointed in a safe direction at all times.
- Avoid placing your face directly over the firearm when installing or adjusting the optic.
- Be cautious of the mounting height; ensure that it does not obstruct your line of sight.
- Do not exceed the manufacturer's recommended weight limit for optics mounted on the offset mount.
- Use appropriate eye protection when shooting with the mounted optic.
- Familiarize yourself with the operation of the optic before use to ensure safe handling.

Instructions for Installation and Usage

Installation Instructions

1. Preparation

- Gather all necessary tools, including a Torx Plus bit driver (IP20 and IP27 included).
- Ensure your AR15 rifle is unloaded and pointed in a safe direction.

2. Mounting the Base

- Locate the top Picatinny rail on your AR15 rifle.
- Align the base of the offset optic mount with the desired position on the rail.
- Secure the base using the twin recoil lugs and clamping screw. Tighten firmly but do not overtighten.

3. Attaching the Optic Plate

- Choose the appropriate optic plate based on your sight type (refer to the product text for compatible plates).
- Align the optic plate with the base and secure it using the provided screws.
- Ensure the optic is firmly attached and does not move when adjusted.

4. Final Adjustments

- Once installed, adjust the optic to your preferred height and angle (35 or 45 degrees).
- Doublecheck all connections to ensure stability.

Usage Instructions

- When using the offset optic, tilt the rifle as needed to acquire the red dot sight.
- Maintain a lower 1/3 cowitness height for optimal alignment with the bore.
- Practice using the offset optic in a safe environment before engaging in live shooting scenarios.

Disposal Instructions

- Dispose of the product in accordance with local regulations regarding electronic waste and metal recycling.
- Do not dispose of the product in regular household waste.
- If applicable, remove batteries and dispose of them separately according to local laws.

Contact Information for Further Support

For any inquiries regarding safety or product issues, please refer to the manufacturer's website or customer service for assistance. It is important to have a point of contact for any safety concerns or product recalls.

By following these guidelines, you can ensure a safe and effective experience with your Arisaka Offset Optic Mount. Always prioritize safety and responsible usage. Thank you for your attention to these important instructions.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk