

# OFFSET OPTIC MOUNT - ARISAKA DEFENSE PLATE #2 STANDARD HEIGHT (1.5"-1.8") OPTIC PLATE

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Rifle Bases](#)

The Patent Pending Arisaka Offset Optic Mount is a modular mounting solution that allows the user to select a 35 or 45 degree offset position for a red dot sight without requiring additional components. The 35 degree position brings the red dot sight up closer to slimmer, smaller scopes, while the 45 degree position provides additional clearance around wider turrets or larger, higher magnification scopes. The Arisaka Offset Optic Mount is designed to be attached to the top Picatinny rail of an AR15 rifle. When the rifle is canted to make use of the offset red dot sight, the optic remains centered over the bore and maintains a lower 1/3 co-witness height. The base and optic plates can be reversed, allowing for use on the left or right side. The base and plates can each be purchased separately or as a combination, providing an upgrade path in the future as users acquire new red dot sights. Weight: 1.9 oz without optic. Length: 1.0" for the base, which occupies three Picatinny slots (twin recoil lugs and clamping screw). Height: The base sits 0.180" above the surface of the Picatinny rail. The mount is CNC machined from 6061-T6 aluminum and MIL-A-8625 Type III hard coat anodized. IP20 and IP27 Torx Plus bit drivers are included with each base. Standard height (for 1.5" to 1.8" scope mounts): Plate 1: Docter, Eotech MRDS, Insight, Meopta, Vortex Venom/Viper, Burris Fastfire III Plate 2: Trijicon RMR, SRO, Holosun 407C, 507C, 508T, Swampfox Kingslayer, Liberty, Justice Plate 4: Leupold Delta Point Pro, JPoint, Shield RMS, RMSc, Swampfox Sentinel, SIG Romeo Zero Plate 5: Aimpoint Micro T1/T2/H1/H2, SIG Romeo 4, 5 (not 5X), Holosun HS403 (not A), HS503, HS515, HS530 Plate 6: Aimpoint Acro Tall height (1.9" to 2.2" scope mounts): Plate 7: Docter, Eotech MRDS, Insight, Meopta, Vortex Venom/Viper, Burris Fastfire III Plate 8: Trijicon RMR, SRO, Holosun 407C, 507C, 508T Plate 10: Leupold Delta Point Pro, JPoint, Shield RMS, RMSc, Swampfox Sentinel, SIG Romeo Zero Plate 11: Aimpoint Micro T1/T2/H1/H2, SIG Romeo 4, 5 (not 5X), Holosun HS403 (not A), HS503, HS515, HS530 Plate 12: Aimpoint Acro



## Attributes

- Name: [ARISAKA DEFENSE PLATE #2 STANDARD HEIGHT \(1.5"-1.8"\) OPTIC PLATE](#)
- Manufacturer: [ARISAKA DEFENSE](#)
- Product no.: 100040407
- Mfr. No.: OOM-P2
- Bullet Style: -
- Caliber: -
- Colour: Black
- Diameter (in): -
- Fits / Used For: -
- Grain: -
- Material: -
- Number of Bases: -
- Style: -
- Delivery weight: 0.034kg
- Shipping height: 25mm
- Shipping width: 57mm
- Shipping length: 114mm

- UPC: 601557939647

## **Item details**

Made in USA

# Table of Contents

- Startpage
- Safety Instruction Guide for OFFSET OPTIC MOUNT ARISAKA DEFENSE PLATE #2
- About Us

# Safety Instruction Guide for OFFSET OPTIC MOUNT ARISAKA DEFENSE PLATE #2

## Introduction

Thank you for choosing the OFFSET OPTIC MOUNT ARISAKA DEFENSE PLATE #2. This guide provides essential safety information and instructions to ensure the safe use and installation of your optic mount. Please read this document carefully before using the product.

## General Safety Guidelines

- **Product Safety:** This product is designed for safe use in accordance with EU regulations. Ensure that you follow all safety instructions to minimize risks.
- **Enhanced Recalls:** Stay informed about product recalls. If you receive notice of a recall, follow the instructions provided for a remedy.
- **Online Shopping:** When purchasing online, ensure that the platform complies with safety regulations similar to those of physical stores.
- **Special Consumer Focus:** This product is not intended for use by children. Keep it out of reach of minors.
- **EU Contact Point:** For any safety inquiries, please refer to the contact information provided by the retailer or manufacturer.
- **Rapid Alerts:** Monitor updates regarding unsafe products through the EU's Safety Gate platform.

## Specific Safety Precautions for Use

- **Installation:** Ensure that the optic mount is securely attached to the Picatinny rail of your rifle before use.
- **Canted Use:** When using the offset red dot sight, ensure the rifle is canted correctly to avoid misalignment.
- **Weight Limit:** Do not exceed the recommended weight for the optic mount. The mount is designed to support optics weighing up to 1.9 oz without additional components.
- **Compatibility:** Confirm that your optic is compatible with the specified height and mounting plates.
- **Inspection:** Regularly inspect the mount and optics for any signs of wear or damage. Do not use if damaged.
- **Proper Handling:** Handle the product with care to avoid dropping or damaging it.

## Instructions for Installation and Usage

1. **Gather Tools:** Ensure you have the necessary tools, including IP20 and IP27 Torx Plus bit drivers, which are included with the base.
2. **Choose Your Plate:** Select the appropriate optic plate based on your scope height:
  - **Standard Height (1.5" to 1.8"):**
    - Plate 1: Docter, Eotech MRDS, Insight, Meopta, Vortex Venom/Viper, Burris Fastfire III
    - Plate 2: Trijicon RMR, SRO, Holosun 407C, 507C, 508T, Swampfox Kingslayer, Liberty, Justice
    - Plate 4: Leupold Delta Point Pro, JPoint, Shield RMS, RMSc, Swampfox Sentinel, SIG Romeo Zero
    - Plate 5: Aimpoint Micro T1/T2/H1/H2, SIG Romeo 4, 5 (not 5X), Holosun HS403 (not A), HS503, HS515, HS530
    - Plate 6: Aimpoint Acro
  - **Tall Height (1.9" to 2.2"):**
    - Plate 7: Docter, Eotech MRDS, Insight, Meopta, Vortex Venom/Viper, Burris Fastfire III
    - Plate 8: Trijicon RMR, SRO, Holosun 407C, 507C, 508T
    - Plate 10: Leupold Delta Point Pro, JPoint, Shield RMS, RMSc, Swampfox Sentinel, SIG Romeo

Zero

- Plate 11: Aimpoint Micro T1/T2/H1/H2, SIG Romeo 4, 5 (not 5X), Holosun HS403 (not A), HS503, HS515, HS530
- Plate 12: Aimpoint Acro

### 3. Mounting Procedure:

- Align the base with the Picatinny rail and secure it using the clamping screws.
- Attach the selected optic plate to the base, ensuring it is firmly in place.
- Verify that the optic is positioned correctly and is stable.

### 4. Final Checks:

After installation, check that the optic is securely mounted and that there is no movement. Perform a function check to ensure proper alignment.

## Disposal Instructions

- Dispose of the product in accordance with local regulations for electronic waste and materials.
- Do not dispose of the product in household waste. Instead, utilize designated recycling facilities.

## Contact Information for Further Support

For any questions or concerns regarding the OFFSET OPTIC MOUNT ARISAKA DEFENSE PLATE #2, please consult the retailer or manufacturer for assistance. They will provide you with the necessary support and information regarding product safety and maintenance.

Thank you for your attention to these safety instructions. By following these guidelines, you can ensure a safe and effective experience with your OFFSET OPTIC MOUNT ARISAKA DEFENSE PLATE #2.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)