

OFFSET OPTIC MOUNT - ARISAKA DEFENSE PLATE #5 STANDARD HEIGHT (1.5"-1.8") OPTIC PLATE

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Rifle Bases](#)

The Patent Pending Arisaka Offset Optic Mount is a modular mounting solution that allows the user to select a 35 or 45 degree offset position for a red dot sight without requiring additional components. The 35 degree position brings the red dot sight up closer to slimmer, smaller scopes, while the 45 degree position provides additional clearance around wider turrets or larger, higher magnification scopes. The Arisaka Offset Optic Mount is designed to be attached to the top Picatinny rail of an AR15 rifle. When the rifle is canted to make use of the offset red dot sight, the optic remains centered over the bore and maintains a lower 1/3 co-witness height. The base and optic plates can be reversed, allowing for use on the left or right side. The base and plates can each be purchased separately or as a combination, providing an upgrade path in the future as users acquire new red dot sights. Weight: 1.9 oz without optic. Length: 1.0" for the base, which occupies three Picatinny slots (twin recoil lugs and clamping screw). Height: The base sits 0.180" above the surface of the Picatinny rail. The mount is CNC machined from 6061-T6 aluminum and MIL-A-8625 Type III hard coat anodized. IP20 and IP27 Torx Plus bit drivers are included with each base. Standard height (for 1.5" to 1.8" scope mounts): Plate 1: Docter, Eotech MRDS, Insight, Meopta, Vortex Venom/Viper, Burris Fastfire III Plate 2: Trijicon RMR, SRO, Holosun 407C, 507C, 508T, Swampfox Kingslayer, Liberty, Justice Plate 4: Leupold Delta Point Pro, JPoint, Shield RMS, RMSc, Swampfox Sentinel, SIG Romeo Zero Plate 5: Aimpoint Micro T1/T2/H1/H2, SIG Romeo 4, 5 (not 5X), Holosun HS403 (not A), HS503, HS515, HS530 Plate 6: Aimpoint Acro Tall height (1.9" to 2.2" scope mounts): Plate 7: Docter, Eotech MRDS, Insight, Meopta, Vortex Venom/Viper, Burris Fastfire III Plate 8: Trijicon RMR, SRO, Holosun 407C, 507C, 508T Plate 10: Leupold Delta Point Pro, JPoint, Shield RMS, RMSc, Swampfox Sentinel, SIG Romeo Zero Plate 11: Aimpoint Micro T1/T2/H1/H2, SIG Romeo 4, 5 (not 5X), Holosun HS403 (not A), HS503, HS515, HS530 Plate 12: Aimpoint Acro



Attributes

- Name: [ARISAKA DEFENSE PLATE #5 STANDARD HEIGHT \(1.5"-1.8"\) OPTIC PLATE](#)
- Manufacturer: [ARISAKA DEFENSE](#)
- Product no.: 100040410
- Mfr. No.: OOM-P5
- Bullet Style: -
- Caliber: -
- Colour: Black
- Diameter (in): -
- Fits / Used For: -
- Grain: -
- Material: -
- Number of Bases: -
- Style: -
- Delivery weight: 0.029kg
- Shipping height: 25mm
- Shipping width: 54mm
- Shipping length: 114mm

- UPC: 601557939678

Item details

Made in USA

Table of Contents

- Startpage
- OFFSET OPTIC MOUNT ARISAKA DEFENSE PLATE #5 STANDARD HEIGHT (1.5"1.8") OPTIC PLATE Consumer Safety Instruction Guide
- About Us

OFFSET OPTIC MOUNT ARISAKA DEFENSE PLATE #5 STANDARD HEIGHT (1.5"1.8") OPTIC PLATE

Consumer Safety Instruction Guide

Introduction

Thank you for choosing the OFFSET OPTIC MOUNT ARISAKA DEFENSE PLATE #5. This guide provides essential safety instructions and information to ensure the safe use and installation of your optic mount. Please read this guide carefully before use to avoid any potential hazards.

General Safety Guidelines

- Ensure that the optic mount is compatible with your firearm and optic before installation.
- Always handle firearms and accessories with care.
- Keep the product out of reach of children and unauthorized users.
- Regularly inspect the optic mount for any signs of wear or damage.
- If you notice any defects or issues, cease use immediately and consult a qualified professional.
- Report any unsafe products or accidents to the relevant authorities.

Specific Safety Precautions for Use

- Use the optic mount only for its intended purpose as described in this guide.
- Do not exceed the recommended weight limit of the optic mount.
- Ensure that all components are securely tightened before use.
- When adjusting the angle of the mount, do so slowly and carefully to avoid injury.
- Avoid using the optic mount in extreme conditions (e.g., severe weather, high humidity) that may affect its performance.
- Always wear appropriate eye and ear protection when handling firearms.

Instructions for Installation and Usage

1. Installation:

- Ensure the firearm is unloaded before beginning the installation.
- Locate the top Picatinny rail on your AR15 rifle.
- Align the base of the optic mount with the desired position on the Picatinny rail.
- Secure the base using the twin recoil lugs and clamping screw provided.
- Ensure the base is level and securely attached.

2. Mounting the Optic:

- Choose the appropriate optic plate based on your red dot sight model (refer to the specifications above).
- Attach the optic plate to the base, ensuring it is properly aligned.
- Tighten the screws to secure the optic plate in place.

3. Adjusting the Angle:

- Decide whether to use the 35degree or 45degree offset position.
- If necessary, reverse the base and optic plates for left or right side use.
- Make sure the optic remains centered over the bore and maintains a lower 1/3 cowitness height.

4. Final Checks:

- Before use, doublecheck that all components are securely fastened and that the optic is properly aligned.
- Test the mount's stability by gently applying pressure to the optic.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in household waste.
- Consider recycling components where applicable.

Contact Information for Further Support

For any inquiries regarding the safety or performance of the OFFSET OPTIC MOUNT ARISAKA DEFENSE PLATE #5, please reach out to the manufacturer or your point of purchase for assistance.

Note: This guide is designed to help you use the product safely and effectively. Always prioritize safety and follow local laws regarding firearm accessories.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk