

MONTANA RIFLE 1999 SHORT ACTION HD SCOPE BASES - EGW

MONTANA RIFLE 1999 SHORT ACTION HD SCOPE BASE 20 MOA

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Rifle Bases](#)

Machined From: Solid 7075 T6 Aircraft Grade Aluminum Finish: Matte Black
Only Compatible with Picatinny or Weaver scope rings. Mounting Hardware:
#6-48 X 1/4 Screws and T-10 Bit Included Torque Specs: 20 in/lbs Center
Spread: 3.65" Overall Length of Mount: 6.670" This mount comes standard
with a bevel on both sides making it ambidextrous. *The center spread is the
distance between the two middle holes, center to center, on your receiver.
These bases sit at approximately 0.35" high. Picatinny cross slots run the full
length of the rail, which gives the shooter flexibility when mounting scope
rings and other accessories. The cross slots are also machined the full width of
the mount and gauged to MIL-STD 1913 specs maintaining tolerances of +/-
.002". After machining; the mounts are tumbled and sand blasted. The
aluminum mounts are Type III hard coat anodized for long lasting durability.
The steel rails are Mil Spec parkerized for a durable rust resistant finish.
Compatible with Picatinny or Weaver scope rings. Add EGW's HD Scope Rings
to make it a complete package! From manufacturing to packaging, EGW's
products are made with pride in the USA. Installation: EGW recommends 20
inch lbs of torque and a drip of blue loctite (loctite is available through our
website and is sold separately).



Attributes

- Name: [EGW MONTANA RIFLE 1999 SHORT ACTION HD SCOPE BASE 20 MOA](#)
- Manufacturer: [EGW](#)
- Product no.: 296000605
- Mfr. No.: 81102
- Action Type: Short
- Colour: Matte Black
- Elevation: 20 MOA
- Material: Aluminum
- Model: 1999
- Number of Bases: 1-Piece
- Style: Picatinny Rail
- Weapon type: Montana Rifle Co.
- Delivery weight: 0.093kg
- Shipping height: 19mm
- Shipping width: 89mm
- Shipping length: 229mm

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for MONTANA RIFLE 1999 SHORT ACTION HD SCOPE BASES](#)
- [About Us](#)

Safety Instruction Guide for MONTANA RIFLE 1999 SHORT ACTION HD SCOPE BASES

Introduction

Thank you for choosing the MONTANA RIFLE 1999 SHORT ACTION HD SCOPE BASES. This guide provides essential safety instructions and information to ensure the safe use and installation of your scope bases. Please read this guide carefully before use.

General Safety Guidelines

- Ensure the product is used only for its intended purpose as a scope mounting base for rifles.
- Always handle firearms and their accessories with care. Follow all safety protocols for firearm usage.
- Store the scope bases in a secure location, away from children and unauthorized users.
- Regularly inspect the scope bases for any signs of wear or damage before each use.
- Report any unsafe conditions or incidents related to this product to the appropriate authorities.

Specific Safety Precautions for Use

- Only use the MONTANA RIFLE 1999 SHORT ACTION HD SCOPE BASES with compatible Picatinny or Weaver scope rings.
- Ensure that the mounting hardware (#648 X 1/4 screws and T10 bit) is included and in good condition before installation.
- Do not exceed the recommended torque specification of 20 inch lbs when installing the scope bases.
- Use blue Loctite to secure the screws, ensuring they do not loosen during use.
- Be cautious of the height of the bases (approximately 0.35 inches) when mounting optics to maintain proper sight alignment.
- Avoid using the scope bases in extreme weather conditions or environments that may compromise their integrity.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools including the T10 bit and a torque wrench.
- Ensure the rifle is unloaded and pointed in a safe direction.

2. Mounting the Scope Bases:

- Align the scope bases with the mounting holes on the receiver of the rifle.
- Insert the screws through the bases into the receiver holes.
- Tighten the screws gradually using the T10 bit, ensuring even pressure across both bases.

3. Applying Torque:

- Use a torque wrench to apply the recommended torque of 20 inch lbs to each screw.
- Apply a small drop of blue Loctite to each screw before final tightening to prevent loosening.

4. Final Inspection:

- After installation, doublecheck that all screws are tightened to the specified torque.
- Confirm that the bases are securely mounted and there is no movement.

5. Mounting Optics:

- Attach compatible Picatinny or Weaver scope rings to the mounted bases.
- Follow the scope ring manufacturer's instructions for proper mounting.

Disposal Instructions

- Dispose of the scope bases and any packaging materials in accordance with local regulations.
- Do not dispose of the product in household waste. Consider recycling options where available.

Contact Information for Further Support

For any inquiries related to safety, installation, or product support, please refer to the manufacturer's website or contact your local distributor.

By following these safety instructions and guidelines, you can ensure a safe and effective experience with your MONTANA RIFLE 1999 SHORT ACTION HD SCOPE BASES. Thank you for your attention to safety and responsible usage.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk