

OFFSET OPTIC MOUNT - ARISAKA DEFENSE OFFSET PLATE, HOLOSON 509T FOR 1.5" TO 1.8" SCOPE MOUNT

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Rifle Bases](#)

The Patent Pending Arisaka Offset Optic Mount is a modular mounting solution that allows the user to select a 35 or 45 degree offset position for a red dot sight without requiring additional components. The 35 degree position brings the red dot sight up closer to slimmer, smaller scopes, while the 45 degree position provides additional clearance around wider turrets or larger, higher magnification scopes. The Arisaka Offset Optic Mount is designed to be attached to the top Picatinny rail of an AR15 rifle. When the rifle is canted to make use of the offset red dot sight, the optic remains centered over the bore and maintains a lower 1/3 co-witness height. The base and optic plates can be reversed, allowing for use on the left or right side. The base and plates can each be purchased separately or as a combination, providing an upgrade path in the future as users acquire new red dot sights. Weight: 1.9 oz without optic. Length: 1.0" for the base, which occupies three Picatinny slots (twin recoil lugs and clamping screw). Height: The base sits 0.180" above the surface of the Picatinny rail. The mount is CNC machined from 6061-T6 aluminum and MIL-A-8625 Type III hard coat anodized. IP20 and IP27 Torx Plus bit drivers are included with each base. Standard height (for 1.5" to 1.8" scope mounts): Plate 1: Docter, Eotech MRDS, Insight, Meopta, Vortex Venom/Viper, Burris Fastfire III Plate 2: Trijicon RMR, SRO, Holosun 407C, 507C, 508T, Swampfox Kingslayer, Liberty, Justice Plate 4: Leupold Delta Point Pro, JPoint, Shield RMS, RMSc, Swampfox Sentinel, SIG Romeo Zero Plate 5: Aimpoint Micro T1/T2/H1/H2, SIG Romeo 4, 5 (not 5X), Holosun HS403 (not A), HS503, HS515, HS530 Plate 6: Aimpoint Acro Tall height (1.9" to 2.2" scope mounts): Plate 7: Docter, Eotech MRDS, Insight, Meopta, Vortex Venom/Viper, Burris Fastfire III Plate 8: Trijicon RMR, SRO, Holosun 407C, 507C, 508T Plate 10: Leupold Delta Point Pro, JPoint, Shield RMS, RMSc, Swampfox Sentinel, SIG Romeo Zero Plate 11: Aimpoint Micro T1/T2/H1/H2, SIG Romeo 4, 5 (not 5X), Holosun HS403 (not A), HS503, HS515, HS530 Plate 12: Aimpoint Acro



Attributes

- Name: [ARISAKA DEFENSE OFFSET PLATE, HOLOSON 509T FOR 1.5" TO 1.8" SCOPE MOUNT](#)
- Manufacturer: [ARISAKA DEFENSE](#)
- Product no.: 430104529
- Mfr. No.: OOM-P13
- Bullet Style: -
- Caliber: -
- Colour: Black
- Diameter (in): -
- Fits / Used For: Holosun
- Grain: -
- Material: -
- Number of Bases: -
- Style: -
- Delivery weight: 0.077kg
- Shipping height: 3mm
- Shipping width: 102mm
- Shipping length: 130mm

- UPC: 601557939869

Item details

Made in USA

Table of Contents

- Startpage
- OFFSET OPTIC MOUNT ARISAKA DEFENSE OFFSET PLATE Safety Instruction Guide
- About Us

OFFSET OPTIC MOUNT ARISAKA DEFENSE OFFSET PLATE Safety Instruction Guide

Introduction

Thank you for choosing the OFFSET OPTIC MOUNT ARISAKA DEFENSE OFFSET PLATE. This product is designed to provide a secure and reliable mounting solution for your optic sight. This guide contains important safety instructions to ensure the safe use and installation of this product, in compliance with the EU General Product Safety Regulation (GPSR).

General Safety Guidelines

- Always read and understand the safety instructions before using the product.
- Ensure that the product is installed correctly to prevent accidents or damage.
- Regularly inspect the mount for any signs of wear or damage.
- Keep the product out of reach of children to prevent misuse.
- Do not use the product for any purpose other than its intended use.
- Report any unsafe products or incidents to the relevant authorities.
- Stay informed about product recalls by checking the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Ensure that the rifle is unloaded before installing or adjusting the optic mount.
- Use appropriate tools for installation to avoid damaging the product.
- Verify that the optic mount is securely attached to the Picatinny rail before use.
- Do not exceed the recommended weight limit for optics to avoid compromising stability.
- When using the offset mount, ensure that the red dot sight is properly aligned with the bore for accurate aiming.
- Avoid using the mount in extreme weather conditions without proper precautions.

Instructions for Installation and Usage

1. Installation Steps:

- Ensure the rifle is pointed in a safe direction and is unloaded.
- Remove the optic from its packaging and inspect for any damage.
- Align the base of the OFFSET OPTIC MOUNT with the desired location on the Picatinny rail.
- Secure the mount using the provided clamping screw and twin recoil lugs. Ensure it is tightly fastened.
- Attach the appropriate optic plate for your red dot sight. Refer to the compatibility list below:
 - **Standard height (for 1.5" to 1.8" scope mounts):**
 - Plate 1: Docter, Eotech MRDS, Insight, Meopta, Vortex Venom/Viper, Burris Fastfire III
 - Plate 2: Trijicon RMR, SRO, Holosun 407C, 507C, 508T, Swampfox Kingslayer, Liberty, Justice
 - Plate 4: Leupold Delta Point Pro, JPoint, Shield RMS, RMS, Swampfox Sentinel, SIG Romeo Zero
 - Plate 5: Aimpoint Micro T1/T2/H1/H2, SIG Romeo 4, 5 (not 5X), Holosun HS403 (not A), HS503, HS515, HS530
 - Plate 6: Aimpoint Acro
 - **Tall height (1.9" to 2.2" scope mounts):**
 - Plate 7: Docter, Eotech MRDS, Insight, Meopta, Vortex Venom/Viper, Burris Fastfire III
 - Plate 8: Trijicon RMR, SRO, Holosun 407C, 507C, 508T
 - Plate 10: Leupold Delta Point Pro, JPoint, Shield RMS, RMS, Swampfox Sentinel, SIG Romeo

Zero

- Plate 11: Aimpoint Micro T1/T2/H1/H2, SIG Romeo 4, 5 (not 5X), Holosun HS403 (not A), HS503, HS515, HS530
 - Plate 12: Aimpoint Acro
- After securing the optic, check that it is firmly attached and correctly aligned.

2. Usage Tips:

- When canted, ensure the optic remains centered over the bore for accurate targeting.
- Adjust the height to maintain a lower 1/3 cowitness height as needed.
- Practice using the offset mount to become familiar with its operation.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in regular household waste.
- Recycle materials whenever possible to minimize environmental impact.

Contact Information for Further Support

For any inquiries or support regarding the OFFSET OPTIC MOUNT ARISAKA DEFENSE OFFSET PLATE, please refer to the manufacturer's website or contact your local distributor.

Thank you for following these safety instructions. Your safety and the safe operation of your equipment are our top priority. Enjoy using your OFFSET OPTIC MOUNT ARISAKA DEFENSE OFFSET PLATE responsibly.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk