

OFFSET OPTIC MOUNT - ARISAKA DEFENSE OFFSET PLATE, HOLOSUN 407K & 507K FOR 1.5"- 1.8" SCOPE MOUNT

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Rifle Bases](#)

The Patent Pending Arisaka Offset Optic Mount is a modular mounting solution that allows the user to select a 35 or 45 degree offset position for a red dot sight without requiring additional components. The 35 degree position brings the red dot sight up closer to slimmer, smaller scopes, while the 45 degree position provides additional clearance around wider turrets or larger, higher magnification scopes. The Arisaka Offset Optic Mount is designed to be attached to the top Picatinny rail of an AR15 rifle. When the rifle is canted to make use of the offset red dot sight, the optic remains centered over the bore and maintains a lower 1/3 co-witness height. The base and optic plates can be reversed, allowing for use on the left or right side. The base and plates can each be purchased separately or as a combination, providing an upgrade path in the future as users acquire new red dot sights. Weight: 1.9 oz without optic. Length: 1.0" for the base, which occupies three Picatinny slots (twin recoil lugs and clamping screw). Height: The base sits 0.180" above the surface of the Picatinny rail. The mount is CNC machined from 6061-T6 aluminum and MIL-A-8625 Type III hard coat anodized. IP20 and IP27 Torx Plus bit drivers are included with each base. Standard height (for 1.5" to 1.8" scope mounts): Plate 1: Docter, Eotech MRDS, Insight, Meopta, Vortex Venom/Viper, Burris Fastfire III Plate 2: Trijicon RMR, SRO, Holosun 407C, 507C, 508T, Swampfox Kingslayer, Liberty, Justice Plate 4: Leupold Delta Point Pro, JPoint, Shield RMS, RMSc, Swampfox Sentinel, SIG Romeo Zero Plate 5: Aimpoint Micro T1/T2/H1/H2, SIG Romeo 4, 5 (not 5X), Holosun HS403 (not A), HS503, HS515, HS530 Plate 6: Aimpoint Acro Tall height (1.9" to 2.2" scope mounts): Plate 7: Docter, Eotech MRDS, Insight, Meopta, Vortex Venom/Viper, Burris Fastfire III Plate 8: Trijicon RMR, SRO, Holosun 407C, 507C, 508T Plate 10: Leupold Delta Point Pro, JPoint, Shield RMS, RMSc, Swampfox Sentinel, SIG Romeo Zero Plate 11: Aimpoint Micro T1/T2/H1/H2, SIG Romeo 4, 5 (not 5X), Holosun HS403 (not A), HS503, HS515, HS530 Plate 12: Aimpoint Acro



Attributes

- Name: [ARISAKA DEFENSE OFFSET PLATE, HOLOSUN 407K & 507K FOR 1.5"- 1.8" SCOPE MOUNT](#)
- Manufacturer: [ARISAKA DEFENSE](#)
- Product no.: 430104534
- Mfr. No.: OOM-P18
- Bullet Style: -
- Caliber: -
- Colour: Black
- Diameter (in): -
- Fits / Used For: Holosun
- Grain: -
- Material: -
- Number of Bases: -
- Style: -
- Delivery weight: 0.077kg
- Shipping height: 3mm
- Shipping width: 102mm
- Shipping length: 127mm

- UPC: 601557940056

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [OFFSET OPTIC MOUNT ARISAKA DEFENSE SAFETY INSTRUCTION GUIDE](#)
- [About Us](#)

OFFSET OPTIC MOUNT ARISAKA DEFENSE SAFETY INSTRUCTION GUIDE

Introduction

Thank you for choosing the OFFSET OPTIC MOUNT ARISAKA DEFENSE OFFSET PLATE, specifically designed for Holosun 407K & 507K scopes. This guide provides essential safety instructions to ensure the safe and effective use of your optic mount. Please read this guide carefully before installation and usage.

General Safety Guidelines

- Always follow the manufacturer's instructions for installation and usage.
- Ensure that the mount is compatible with your specific firearm and optic.
- Inspect the mount regularly for any signs of wear or damage.
- Do not exceed the weight limit specified for the mount.
- Keep the mount and associated components out of reach of children and unauthorized users.
- Report any unsafe products or accidents to the appropriate authorities.
- Stay informed about safety recalls through the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Ensure that the rifle is unloaded before installing the optic mount.
- Use appropriate tools as specified in the installation instructions.
- Avoid using the mount in extreme environmental conditions unless specified.
- Be cautious of sharp edges during installation and handling.
- Do not modify the mount or its components, as this may compromise safety.
- Always verify that the optic is securely mounted before use.
- When using the offset red dot sight, ensure it is properly aligned with the bore.

Instructions for Installation and Usage

1. Preparation

- Ensure you have the necessary tools, including IP20 and IP27 Torx Plus bit drivers (included).
- Gather all components of the OFFSET OPTIC MOUNT.

2. Installation Steps

- **Step 1:** Ensure the rifle is unloaded and placed on a stable surface.
- **Step 2:** Identify the top Picatinny rail on your AR15 rifle.
- **Step 3:** Align the base of the mount with the desired position on the Picatinny rail.
- **Step 4:** Secure the base using the clamping screw and twin recoil lugs provided. Ensure it is tightly fastened.
- **Step 5:** Choose the appropriate optic plate based on your scope type (refer to the compatibility list).
- **Step 6:** Attach the selected optic plate to the base, ensuring it is properly aligned.
- **Step 7:** Tighten the screws to secure the optic plate in place.

3. Usage Instructions

- When using the offset optic, tilt the rifle to engage the red dot sight.
- Ensure that the optic remains centered over the bore during use.
- Regularly check the alignment and security of the optic during shooting sessions.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the mount in general household waste.
- Consider recycling options for metal components if available.

Contact Information for Further Support

For any inquiries regarding safety or support, please reach out to the designated EU contact point for assistance.

Thank you for your attention to these safety guidelines. Proper use and maintenance of your OFFSET OPTIC MOUNT will enhance your shooting experience while ensuring your safety and that of others.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk