

OFFSET OPTIC MOUNT - ARISAKA DEFENSE OFFSET PLATE, TRIJICON RMRCC FOR 1.5" TO 1.8" SCOPE MOUNT

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Rifle Bases](#)

The Patent Pending Arisaka Offset Optic Mount is a modular mounting solution that allows the user to select a 35 or 45 degree offset position for a red dot sight without requiring additional components. The 35 degree position brings the red dot sight up closer to slimmer, smaller scopes, while the 45 degree position provides additional clearance around wider turrets or larger, higher magnification scopes. The Arisaka Offset Optic Mount is designed to be attached to the top Picatinny rail of an AR15 rifle. When the rifle is canted to make use of the offset red dot sight, the optic remains centered over the bore and maintains a lower 1/3 co-witness height. The base and optic plates can be reversed, allowing for use on the left or right side. The base and plates can each be purchased separately or as a combination, providing an upgrade path in the future as users acquire new red dot sights. Weight: 1.9 oz without optic. Length: 1.0" for the base, which occupies three Picatinny slots (twin recoil lugs and clamping screw). Height: The base sits 0.180" above the surface of the Picatinny rail. The mount is CNC machined from 6061-T6 aluminum and MIL-A-8625 Type III hard coat anodized. IP20 and IP27 Torx Plus bit drivers are included with each base. Standard height (for 1.5" to 1.8" scope mounts): Plate 1: Docter, Eotech MRDS, Insight, Meopta, Vortex Venom/Viper, Burris Fastfire III Plate 2: Trijicon RMR, SRO, Holosun 407C, 507C, 508T, Swampfox Kingslayer, Liberty, Justice Plate 4: Leupold Delta Point Pro, JPoint, Shield RMS, RMSc, Swampfox Sentinel, SIG Romeo Zero Plate 5: Aimpoint Micro T1/T2/H1/H2, SIG Romeo 4, 5 (not 5X), Holosun HS403 (not A), HS503, HS515, HS530 Plate 6: Aimpoint Acro Tall height (1.9" to 2.2" scope mounts): Plate 7: Docter, Eotech MRDS, Insight, Meopta, Vortex Venom/Viper, Burris Fastfire III Plate 8: Trijicon RMR, SRO, Holosun 407C, 507C, 508T Plate 10: Leupold Delta Point Pro, JPoint, Shield RMS, RMSc, Swampfox Sentinel, SIG Romeo Zero Plate 11: Aimpoint Micro T1/T2/H1/H2, SIG Romeo 4, 5 (not 5X), Holosun HS403 (not A), HS503, HS515, HS530 Plate 12: Aimpoint Acro



Attributes

- Name: [ARISAKA DEFENSE OFFSET PLATE, TRIJICON RMRCC FOR 1.5" TO 1.8" SCOPE MOUNT](#)
- Manufacturer: [ARISAKA DEFENSE](#)
- Product no.: 430104537
- Mfr. No.: OOM-P21
- Bullet Style: -
- Caliber: -
- Color: -
- Diameter (in): -
- Fits / Used For: -
- Grain: -
- Material: -
- Number of Bases: -
- Style: -
- Delivery weight: 0.077kg
- Shipping height: 3mm
- Shipping width: 102mm
- Shipping length: 127mm

- UPC: 601557940087

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for OFFSET OPTIC MOUNT ARISAKA DEFENSE OFFSET PLATE
- About Us

Safety Instruction Guide for OFFSET OPTIC MOUNT ARISAKA DEFENSE OFFSET PLATE

Introduction

Thank you for choosing the Arisaka Offset Optic Mount. This product is designed to enhance your shooting experience by providing a modular and flexible mounting solution for your optics. To ensure safe and effective use, please read and follow the safety instructions outlined in this guide.

General Safety Guidelines

- Ensure that the mount is compatible with your rifle and optic specifications before installation.
- Always handle firearms and accessories with care and respect. Treat every firearm as if it is loaded.
- Keep the mount and optic out of reach of children and unauthorized users.
- Regularly inspect the mount for any signs of wear or damage. If any issues are found, discontinue use immediately.
- Follow all local laws and regulations regarding firearm accessories and usage.

Specific Safety Precautions for Use

- When using the offset mount, ensure that it is securely attached to the Picatinny rail before firing.
- Do not exceed the recommended weight limit for optics mounted on the offset plate to avoid failure.
- Be aware of your surroundings and ensure a safe shooting environment when using your firearm.
- Always wear appropriate eye and ear protection while shooting.
- If you experience any difficulty with the mount or optic, seek assistance from a qualified gunsmith or professional.

Instructions for Installation and Usage

1. Installation

- Ensure that your rifle is unloaded and pointed in a safe direction.
- Select the appropriate base and optic plate for your scope. Refer to the compatibility list below:
 - **Standard height (for 1.5" to 1.8" scope mounts):**
 - Plate 1: Docter, Eotech MRDS, Insight, Meopta, Vortex Venom/Viper, Burris Fastfire III
 - Plate 2: Trijicon RMR, SRO, Holosun 407C, 507C, 508T, Swampfox Kingslayer, Liberty, Justice
 - Plate 4: Leupold Delta Point Pro, JPoint, Shield RMS, RMS, Swampfox Sentinel, SIG Romeo Zero
 - Plate 5: Aimpoint Micro T1/T2/H1/H2, SIG Romeo 4, 5 (not 5X), Holosun HS403 (not A), HS503, HS515, HS530
 - Plate 6: Aimpoint Acro
 - **Tall height (1.9" to 2.2" scope mounts):**
 - Plate 7: Docter, Eotech MRDS, Insight, Meopta, Vortex Venom/Viper, Burris Fastfire III
 - Plate 8: Trijicon RMR, SRO, Holosun 407C, 507C, 508T
 - Plate 10: Leupold Delta Point Pro, JPoint, Shield RMS, RMS, Swampfox Sentinel, SIG Romeo Zero
 - Plate 11: Aimpoint Micro T1/T2/H1/H2, SIG Romeo 4, 5 (not 5X), Holosun HS403 (not A), HS503, HS515, HS530
 - Plate 12: Aimpoint Acro
- Attach the selected base to the Picatinny rail using the provided clamping screw and twin recoil lugs.
- Secure the optic plate to the base, ensuring it is properly aligned for your preferred shooting

position (35 or 45 degrees).

- Tighten all screws to the manufacturer's specifications without overtightening.

2. Usage

- Once installed, verify that the optic is properly zeroed according to the manufacturer's instructions.
- When transitioning to the offset sight, ensure that the rifle is canted appropriately to maintain a clear view through the optic.
- Maintain a proper shooting stance and grip to ensure control of the rifle while using the offset mount.

Disposal Instructions

- Dispose of the product according to local regulations for electronic and metal waste.
- Do not dispose of the product in regular household waste.
- Check with local waste management authorities for proper disposal methods.

Contact Information for Further Support

For any questions or concerns regarding the use or safety of the OFFSET OPTIC MOUNT ARISAKA DEFENSE OFFSET PLATE, please contact your local distributor or refer to the manufacturer's website for additional support and resources.

By following these guidelines, you can ensure a safe and enjoyable experience with your Arisaka Offset Optic Mount. Thank you for prioritizing safety and compliance with the EU General Product Safety Regulation.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk