

ALUMA-HYDE CLEAN OUT NOZZLES - BROWNELLS CLEAN OUT NOZZLE, SINGLE

[Gunsmith Tools](#) > [Metal Prep & Coloring](#) > [Paint Finishes](#) > [Replacement Nozzles](#)

Lets full pressure blow through a plugged pickup tube to clean it out. Once clear, install a Replacement Nozzle to continue spraying.



Attributes

- Name: [BROWNELLS CLEAN OUT NOZZLE, SINGLE](#)
- Manufacturer: [BROWNELLS](#)
- Product no.: 430107431
- Mfr. No.: CON-SINGLE
- Delivery weight: 0.005kg
- Shipping height: 25mm
- Shipping width: 25mm
- Shipping length: 25mm
- UPC: 050806000803

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for ALUMAHYDE CLEAN OUT NOZZLES
- About Us

Safety Instruction Guide for ALUMAHYDE CLEAN OUT NOZZLES

Introduction

Thank you for choosing the ALUMAHYDE CLEAN OUT NOZZLES by BROWNELLS. This guide provides essential safety instructions to ensure the safe and effective use of the product. Please read this guide carefully before using the nozzles.

General Safety Guidelines

- Ensure safe use of the product by following all instructions in this guide.
- Always use the product for its intended purpose; the Clean Out Nozzle is not intended for spraying.
- Keep this product out of reach of children and vulnerable individuals.
- Regularly check for updates on product safety and recalls through the EU's Safety Gate platform.
- Report any unsafe products or accidents to the appropriate authorities.

Specific Safety Precautions for Use

- Do not use the Clean Out Nozzle if it appears damaged or malfunctioning.
- Avoid using the nozzle in environments with flammable materials.
- Ensure adequate ventilation when using the nozzle to prevent the buildup of harmful fumes.
- Use personal protective equipment (PPE) such as gloves and safety goggles when handling the product.
- Always point the nozzle away from yourself and others when using it.

Instructions for Installation and Usage

1. Preparation:

- Before installation, ensure that the area is clean and free from obstructions.
- Wear appropriate PPE to protect yourself during installation and use.

2. Installation:

- Remove the existing nozzle from the pickup tube by turning it counterclockwise.
- Align the threads of the Clean Out Nozzle with the pickup tube.
- Turn the Clean Out Nozzle clockwise until it is securely attached.

3. Usage:

- Once installed, apply full pressure to blow through the plugged pickup tube.
- Monitor the flow of air to ensure the tube is clear.
- After clearing the tube, remove the Clean Out Nozzle by turning it counterclockwise.
- Install a Replacement Nozzle to continue spraying if needed.

Disposal Instructions

- Dispose of the Clean Out Nozzle in accordance with local regulations regarding nonhazardous waste.
- Do not dispose of the product in household waste; check for designated disposal facilities in your area.

Contact Information for Further Support

For further inquiries or support regarding the ALUMAHYDE CLEAN OUT NOZZLES, please refer to the manufacturer's contact information provided with the product packaging.

By adhering to these safety instructions, you can ensure a safe and effective experience with your ALUMAHYDE CLEAN OUT NOZZLES. Thank you for your attention to safety.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk