

2 CAVITY PISTOL BULLET MOLDS - LEE PRECISION 476 LINEBAUGH (0.476") 400GR ROUND NOSE DOUBLE CAVITY MOLD

[Reloading](#) > [Bullet Casting](#) > [Casting Moulds](#) > [Handgun Moulds](#)

All molds for pistol calibers are double cavity to speed casting. All Lee mould blocks are made from aluminum because of the exceptional moulding qualities. The mould cavities are CNC machined for unmatched roundness and size control. Most bullets from Lee moulds can be used as cast without sizing. Handles and sprue plate are included.



Attributes

- Name: [LEE PRECISION 476 LINEBAUGH \(0.476"\) 400GR ROUND NOSE DOUBLE CAVITY MOLD](#)
- Manufacturer: [LEE PRECISION](#)
- Product no.: 430108473
- Mfr. No.: 90241
- Bullet Style: Round Nose (RN)
- Bullet Weight (Grains): 400
- Caliber: 476 Linebaugh
- Cavities: 2
- Diameter (in): 0.476
- Delivery weight: 0.396kg
- Shipping height: 51mm
- Shipping width: 66mm
- Shipping length: 269mm
- UPC: 734307902414

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for 2 Cavity Pistol Bullet Molds Lee Precision 476 Linebaugh
- About Us

Safety Instruction Guide for 2 Cavity Pistol Bullet Molds Lee Precision 476 Linebaugh

Introduction

Thank you for choosing the 2 Cavity Pistol Bullet Molds Lee Precision 476 Linebaugh. This guide provides important safety information and instructions to ensure safe usage of the product. Please read this guide thoroughly before using the product.

General Safety Guidelines

- Ensure safe use of the product by following all instructions provided.
- Always handle the molds with care to avoid injury.
- Keep the molds out of reach of children and vulnerable individuals.
- Be aware of potential hazards associated with casting bullets, including hot surfaces and lead exposure.
- Regularly check for updates on product recalls or safety notices via the EU Safety Gate platform.
- Report any unsafe products or accidents to the relevant authorities.

Specific Safety Precautions for Use

- Always wear appropriate personal protective equipment (PPE), including gloves and safety goggles, when using the molds.
- Ensure the work area is wellventilated to avoid inhalation of fumes.
- Do not exceed the recommended temperature when melting lead to prevent hazards.
- Avoid contact with hot surfaces to prevent burns.
- Store the molds in a cool, dry place when not in use to maintain their integrity.

Instructions for Installation and Usage

1. Preparation:

- Ensure the work area is clean and free from any flammable materials.
- Gather all necessary tools and materials before starting.

2. Setting Up the Molds:

- Place the mold on a stable, heatresistant surface.
- Ensure the handles are securely attached before use.

3. Melting Lead:

- Use a lead melting pot suitable for the intended temperature.
- Monitor the temperature closely to avoid overheating the lead.

4. Casting Bullets:

- Pour the melted lead into the mold cavities carefully to avoid spills.
- Allow the lead to cool and solidify before removing the bullets from the mold.
- Use caution when opening the mold, as it may still be hot.

5. PostUsage Care:

- Clean the molds according to the manufacturer's instructions to prevent residue buildup.
- Inspect the molds for any signs of damage before each use.

Disposal Instructions

- Dispose of any lead scraps and waste in accordance with local regulations.
- Do not dispose of lead in regular household waste.
- Follow local guidelines for the safe disposal of metal products.

Contact Information for Further Support

For any inquiries or additional support regarding the 2 Cavity Pistol Bullet Molds Lee Precision 476 Linebaugh, please refer to the manufacturer's contact information provided with the product packaging.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk