

AR-15 SOLID ADJUSTABLE GAS BLOCK - SUPERLATIVE ARMS AR-15 SOLID TITANIUM ADJUSTABLE GAS BLOCK .875" GRAY

[Rifle Parts](#) > [Gas System Parts](#) > [Gas Blocks](#)

The Superlative Arms patented "Bleed Off", direct impingement, gas block for the AR15 platform adjusts the gas flow by bleeding the gas out of the block instead of restricting the flow like conventional adjustable blocks. Results: The pressure used in the block is reduced only to the amount required to drive the bolt carrier. The remaining gas / pressure are bled out of the block allowing the system to run much cleaner and cooler. Reduction of felt recoil. Patented adjustment detent is located outside of the block and therefore no contamination. The gas adjustment screw does not restrict the gas flow; therefore there is no erosion or seizing of the screw / no loss of detent due to carbon build up. Although it is removable, we have added a safety mechanism, which stops you from unintentionally backing the screw all the way out. When using SBR's and / or suppressors the bleed off port allows the excessive pressure to be exhausted out of the block reducing blow back.

Data: Gas Block Material: 416 SS Barrel Diameter: 0.625" Weight: 1.37 oz. Length: 1.00" Attachment Type: Solid Gas Adjustment: 30 Locked Positions, Front Of Block Bleed Off Port: Front Of Block Included: Gas Block - Assembled (2) 10-32 x 3/16" Set Screws (1) Gas Tube Roll Pins (1) 3/32 X 6" L-Shaped Hex Keys Installation Instructions & QR code for video tutorial



Attributes

- Name: [SUPERLATIVE ARMS AR-15 SOLID TITANIUM ADJUSTABLE GAS BLOCK .875" GRAY](#)
- Manufacturer: [SUPERLATIVE ARMS](#)
- Product no.: 430109760
- Mfr. No.: SABO-DI-875SGT
- Inside Diameter: .875
- Material: Titanium
- Style: Screw
- Weapon type: AR-15
- Delivery weight: 0.454kg
- Shipping height: 51mm
- Shipping width: 95mm
- Shipping length: 191mm
- UPC: 850011846483

Item details

Made in USA
US export classification: 0A501.x

Table of Contents

- Startpage
- Safety Instruction Guide for AR15 Solid Adjustable Gas Block
- About Us

Safety Instruction Guide for AR15 Solid Adjustable Gas Block

Introduction

Thank you for choosing the Superlative Arms AR15 Solid Adjustable Gas Block. This guide provides important safety instructions and guidelines to ensure the safe use and installation of this product. Please read this document carefully before using the gas block.

General Safety Guidelines

- Ensure that the gas block is compatible with your AR15 platform before installation.
- Always follow local laws and regulations regarding firearm modifications and usage.
- Handle all firearms with care and ensure they are unloaded when installing or modifying components.
- Keep the gas block and its components out of reach of children and unauthorized users.
- Regularly inspect the gas block for any signs of wear or damage before each use.
- Report any unsafe product experiences or accidents to the appropriate authorities.

Specific Safety Precautions for Use

• Installation Precautions:

- Ensure that the firearm is completely unloaded before starting the installation process.
- Use appropriate tools and wear safety goggles to protect your eyes during installation.

• Operational Precautions:

- Always verify that the gas adjustment screw is securely in place before operating the firearm.
- Avoid adjusting the gas block while the firearm is hot to prevent burns or damage.
- When using suppressors or shortbarreled rifles (SBRs), monitor the bleedoff port to ensure proper functioning and safety.

• Maintenance Precautions:

- Regularly clean the gas block to prevent carbon buildup, which can affect performance.
- Inspect the adjustment detent and gas adjustment screw for any signs of erosion or damage.

Instructions for Installation and Usage

1. Preparation:

- Gather all necessary tools, including a set of hex keys, and ensure you have a clean working area.
- Confirm that you have the following components:
 - Gas Block (Assembled)
 - (2) 1032 x 3/16" Set Screws
 - (1) Gas Tube Roll Pin
 - (1) 3/32 X 6" LShaped Hex Key

2. Installation Steps:

- Ensure the firearm is unloaded.
- Remove the existing gas block from the barrel, if applicable.
- Position the new gas block over the barrel, aligning it with the gas port.

- Secure the gas block using the provided set screws, tightening them evenly to avoid misalignment.
- Insert the gas tube roll pin into the designated hole to secure the gas tube, if applicable.
- Adjust the gas adjustment screw to your desired setting, ensuring it is not fully removed to avoid loss.
- Verify that the bleedoff port is unobstructed and correctly positioned.

3. Usage:

- After installation, test the gas block with a few rounds to ensure proper function.
- Monitor the firearm's operation and adjust the gas flow as necessary for optimal performance.

Disposal Instructions

- Dispose of any packaging materials in accordance with local waste management regulations.
- If the gas block or its components become damaged beyond repair, follow local guidelines for the disposal of metal and other materials.
- Do not dispose of the gas block in regular household waste; instead, recycle where possible.

Contact Information for Further Support

For any inquiries regarding the product, please refer to the manufacturer's contact information provided with your purchase.

Thank you for your attention to these safety guidelines. Your safety and the safe operation of your firearm are our top priorities.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk