

FRONT SIGHT TOOL for GLOCK® - HIVIZ FRONT SIGHT TOOL

[Gunsmith Tools](#) > [Handgun Tools](#) > [Sight Tools](#)

Installs and removes HIVIZ front sights for Glock pistols. Large, hex-shaped grasping surface gives you a secure purchase and plenty of leverage. Also fits Walther P99, Smith & Wesson SW99, and other pistols with sights that use 3/16" hex head screws.



Attributes

- Name: [HIVIZ FRONT SIGHT TOOL](#)
- Manufacturer: [HIVIZ](#)
- Product no.: 638000188
- Mfr. No.: GLOCK-TL
- Model: Universal Handguns
- Weapon type: Glock
- Delivery weight: 0.023kg
- Shipping height: 10mm
- Shipping width: 56mm
- Shipping length: 157mm
- UPC: 613485586718

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [FRONT SIGHT TOOL for GLOCK® HIVIZ FRONT SIGHT TOOL Safety Instructions](#)
- [About Us](#)

FRONT SIGHT TOOL for GLOCK® HIVIZ FRONT SIGHT TOOL Safety Instructions

Introduction

Thank you for choosing the FRONT SIGHT TOOL for GLOCK® HIVIZ FRONT SIGHT TOOL. This tool is designed to assist in the installation and removal of HIVIZ front sights for Glock pistols and other compatible firearms. Please read these safety instructions carefully to ensure safe and effective use of the product.

General Safety Guidelines

- Always read and follow the manufacturer's instructions before using the tool.
- Ensure that the firearm is unloaded and pointed in a safe direction before using the tool.
- Keep the tool out of reach of children and unauthorized users.
- Inspect the tool for any damage before use. Do not use if damaged.
- Use the tool only for its intended purpose as described in this manual.
- Report any unsafe conditions or incidents to the appropriate authorities.

Specific Safety Precautions for Use

- Use eye protection when using the tool to prevent injury from flying debris.
- Ensure a stable work surface when performing installations or removals.
- Avoid excessive force when using the tool to prevent damage to the firearm or the tool itself.
- Do not use the tool if you are under the influence of drugs or alcohol.
- If you are unfamiliar with firearm maintenance, seek assistance from a qualified professional.

Instructions for Installation and Usage

1. Preparation

- Ensure your firearm is unloaded and pointed in a safe direction.
- Gather all necessary tools, including the FRONT SIGHT TOOL.

2. Installation of HIVIZ Front Sight

- Locate the front sight on your Glock pistol.
- Use the FRONT SIGHT TOOL to loosen the hex head screw securing the front sight.
- Carefully remove the old front sight.
- Align the new HIVIZ front sight with the mounting slot.
- Insert the hex head screw and tighten it securely using the FRONT SIGHT TOOL. Do not overtighten.

3. Removal of HIVIZ Front Sight

- Locate the hex head screw on the front sight.
- Use the FRONT SIGHT TOOL to loosen the screw.
- Carefully remove the front sight from the mounting slot.

4. PostInstallation Check

- Ensure that the front sight is securely attached.
- Perform a visual inspection to confirm that there are no loose parts.

Disposal Instructions

- Dispose of any packaging materials in accordance with local regulations.
- If the tool becomes damaged beyond repair, dispose of it in a manner that prevents any potential harm to the environment or individuals.

Contact Information for Further Support

For safety inquiries or further assistance, please refer to the manufacturer's contact details provided on the product packaging or the manufacturer's website.

By following these safety instructions, you can ensure a safe and effective experience using the FRONT SIGHT TOOL for GLOCK® HIVIZ FRONT SIGHT TOOL. Thank you for prioritizing safety and responsible firearm maintenance.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk